

# DAKOTA ULTRASONICS

## Engine Re-builders // Racing Sonic Testers, Transducers & Accessories - Price List

Date: 05/01/08

The **PR-8 Series** of gauges are packaged in an all aluminum case making them the most durable gauges on the market.

Models	Features	Part #	Price US
<b>PR-8<sup>2</sup></b>	Field Calibration of all materials, High Speed Scanning, and Backlit Display.	Z-102-0002	1095.00
<b>PR-8V</b>	All the features of the PR-8 <sup>2</sup> with a Time Based B-Scan that will graphically draw the blind surface of a cylinder wall to show corrosion. Measures through paint and eliminates the thickness of the paint which causes errors on roll cages and chassis tubing. Data Logger – Stores 12,000 readings & B-Scans. Selectable data structure option for engines, or general tubing inspection.	Z-158-0001	1595.00
<b>Kit Includes:</b>	Unit, Standard Transducer, Couplant, Manual, Plastic Carrying Case and AA Batteries. PC Engine Mapping Software and Transfer Cable included with PR-8V gauge.		

### 5.0 MHz Dual Element Transducers (Cast Iron)

**Materials Used:** Cast Iron, Steel, Glass, Thin Plastics

**Applications Used:** Cylinders, Heads, Decks, Tubing, Body panels, Wind shields

**Most Common:** Covers majority of all iron automotive applications.

Diameter	Part #	Comments	Ø	Connector	Radius	Entry	Price \$
3/16"	T-121-2100	Low Profile		Potted	0"	Side	255.00
1/4"	T-102-2000	Chassis tubing-Standard	Ø	Potted	0"	Side	255.00
1/4"	T-102-2700	Thru-paint Chassis tubing – PR-8V (E-E)	Ø	Potted	0"	Side	295.00
1/4"	T-162-2110	Low Profile 1" wand for cast iron head ports	Ø	Potted	.6"	Side	265.00
1/4"	T-132-2110	Low Profile 9" wand for cast iron head ports		Potted	.6"	Side	265.00
1/2"	T-104-2120	Cylinder Probe - Iron	Ø	Potted	2"	Side	265.00

**Note:** The ranges below are general ranges only, as the cast consistency varies from batch to batch. The more consistent the cast material is, the easier it is to pass sound through. If the material range is not specified below, this indicates that the probe frequency is not a good match for the material.

Diameter	Mode	Range (ST=Steel) (CI = Cast Iron) (CA= Cast Aluminum)	Wearface Diameter	Crystal Diameter
3/16"	P-E	.060" to 2.0" ST	1/4"	3/16"
3/16"	P-E	.060" to .500" CI	1/4"	3/16"
1/4"	P-E	.040" to 6.0" ST	3/8"	1/4"
1/4"	P-E	.040" to .650" CI	3/8"	1/4"

DAKOTA ULTRASONICS

1500 Green Hills Road, #107 Scotts Valley, CA 95066

Phone: (831) 431-9722 Fax: (831) 431-9723 www.dakotaultrasonics.com

Prices subject to change without notice: please call for an updated price list.

1/4"	E-E PR-8V	.050" to 1.0" ST	3/8"	1/4"
1/2"	P-E	.050" to 15.0" ST	5/8"	1/2"
1/2"	P-E	.050" to 1.5" CI	3/8"	1/4"
<b>Note:</b> Additional High Damped versions are available in the above configurations for an additional charge. These items are custom builds only.				

**10.0 MHz Dual Element Transducers (Cast Aluminum)**  
**Materials Used:** Cast Iron, Steel, Glass, Thin Plastics  
**Applications Used:** Cylinders , Heads, Decks, Tubing, Body panels, Wind shields  
**Most Common:** Covers majority of all aluminum automotive applications.

Diameter	Part #	Comments	Connector	Radius	Entry	Price \$
3/16"	T-101-4000	NHRA chassis tubing	Potted	0"	Side	275.00
1/4"	T-162-4110	Low Profile 1" wand for cast alum. head ports	Potted	.6"	Side	275.00
1/4"	T-132-4110	Low Profile 9" wand for cast alum. head ports	Potted	.6"	Side	275.00
1/2"	T-104-4120	Cylinder Probe – Alum.	Potted	2"	Side	275.00

**Note:** The ranges below are general ranges only, as the cast consistency varies from batch to batch. The more consistent the cast material is, the easier it is to pass sound through. If the material range is not specified below, this indicates that the probe frequency is not a good match for the material.

Diameter	Mode	Range (ST=Steel) (CI = Cast Iron) (CA= Cast Aluminum)	Wearface Diameter	Crystal Diameter
3/16"	P-E	.040" to 2.0" ST	1/4"	3/16"
3/16"	P-E	.060" to .500" CA	1/4"	3/16"
1/4"	P-E	.040" to 6.0" ST	3/8"	1/4"
1/4"	P-E	.040" to 1.0" CA	3/8"	1/4"
1/2"	P-E	.050" to 10.0" ST	5/8"	1/2"
1/2"	P-E	.050" to 1.5" CA	3/8"	1/4"

**Note:** Additional High Damped versions are available in the above configurations for an additional charge. These items are custom builds only.

### Accessory Items

Instrument & Carrying Cases			
Part #	Description	Comments	Price \$
F-100-0004	PR-8 Nylon Instrument Case		55.00
F-112-0005	PR-8 <sup>2</sup> Series Nylon Case		55.00
F-149-0001	PR-8V Instrument Case		75.00
A-100-6002	Plastic Carrying Brief Case	All Models	35.00

Couplant			
Part #	Description	Comments	Price \$
V-000-0001	4 oz bottle		7.00
V-000-0003	12 oz bottle		12.00
V-000-0004	1 gallon		85.00

<b>Calibration Blocks</b>			
<b>Part #</b>	<b>Description</b>	<b>Mat'l Type</b>	<b>Price \$</b>
X-000-0001	5 Step - .100" to .500"	4340 Steel	185.00
X-000-0002	4 Step - .250 to 1.0"	4340 Steel	185.00

<b>Misc. Accessories</b>			
<b>Part #</b>	<b>Description</b>	<b>Comments</b>	<b>Price \$</b>
F-000-7001	Bell Shaped Spring Loaded Probe Holder (V-Block)	Std Can Style Probes Only	150.00
F-102-0001	Hammer Transducer (Cylinder Kit) with water path.	Used for with the B-Scan feature.	425.00

<b>Data Cables</b>			
<b>Part #</b>	<b>Description</b>	<b>Comments</b>	<b>Price \$</b>
N-306-0010	6 foot RS232 (DB-9 to Lemo)	PR-8V	100.00
N-402-0510	USB to Serial Adapter	PR-8V	45.00

<b>Software &amp; Data CD</b>			
<b>Part #</b>	<b>Description</b>	<b>Comments</b>	<b>Price \$</b>
A-158-7001	PR-8Vsonicview Software CD (note: Software available for download on our website at no charge)	PR-8V	30.00