


Dakota NDT

Single Element Specialty Thickness Gauges, Transducers & Accessories - Price List

Date: 05/01/24


The **Specialty Series** of gauges are packaged in an all aluminum case.

Models	Features	Part #	Price US
<p>PMX4-DL</p>  <p>Formerly: HPX-DL+</p>	<p>A-Scan waveform (RF & Rectified views), Large Digits, and time based B-Scan views. Multiple calibration options, and selectable material list. Selectable pulser voltage and damping options. Time dependent gain (TDG) with adjustable slope and start settings. Selectable mode options: Pulse-Echo (P-E), Echo-Echo(E-E), and Echo-Echo Verify (E-EV) options. Alarm Mode (Hi & Lo Limits), Hi Speed Scan Mode, multiple Languages, Setups (64 user defined), Data Logger (4 GB SD card), USB-C connectivity, and screen capture to (.tif) images. Probe options: Custom Delay-Line & Contact.</p>	Z-225-0002	3650.00
Kits Includes:	Unit, custom 1" Delay Line Transducer (Rubber Delay Line) & Cable, Couplant, Manual, Certificate of Calibration, AA Batteries and Plastic Carrying Case. PC Software (download) & transfer cable included.		

SINGLE ELEMENT DELAY LINE TRANSDUCERS (HPD) – HIGH PENETRATION



Element Size (Dia.)	A	B
1.00"	1.060"	2.800"



Description:	Replaceable rubber delay line low frequency transducers.
Used:	Fiberglass, composite plastics, plastics, carbon fiber, rubber conveyor belts.
Damping:	Medium
Connector:	BNC top connect only
Price:	\$1050.00 US

Dakota NDT - 1500 Green Hills Road, #107 Scotts Valley, CA 95066
 Phone: (831) 431-9722 Fax: (831) 431-9723 www.dakotaultrasonics.com
 Prices subject to change without notice: please call for an updated price list.
 ⚠️ "WARNING: Cancer and Reproductive Harm – www.p65warnings.ca.gov"


Element Size	500 kHz	1.0 MHz	2.25 MHz	3.5 MHz
.500" DIA. (a)	-	-	-	-
.750" DIA.	-	-	-	-
1.00" DIA.	HPD1005 T-857-8608 (T)	-	-	-

Ordering Example: Model #: HPD1005B = HPD 1.0" x 500 kHz BNC, or PT# T-407-8605

SINGLE ELEMENT CONTACT TRANSDUCERS (SLM) – HIGH WEAR



Element Size (Dia.)	A	B
.500"	1.055"	1.230"
.750"	1.268"	1.430"
1.00"	1.555"	1.430"



Description:	High wear/resolution contact transducers with extended stainless steel ring.
Used:	Rough surfaces, Castings, Billets, and Extruded Parts.
Damping:	Medium
Connectors:	BNC (B), Lemo 1 (L) *Specify connector type after part #
Price:	\$385.00 US **\$435.00 (P) Composite option - 1MHz & 3.5MHz only available with Composite.


Element Size	**1.0 MHz	**2.25 MHz	**3.5 MHz	**5.0 MHz
.500" DIA. (a)	PSLM501 T-8040-0868	SLM5025 T-8040-1878	PSLM5035 -	SLM5050 T-8040-2878
.750" DIA.	PSLM751 T-8060-0868	SLM7525 T-8060-1878	PSLM7535 -	SLM7550 T-8060-2878
1.00" DIA.	PSLM101 T-8070-0868	SLM1025 T-8070-1878	PSLM1035 -	SLM1050 T-8070-2878

Ordering Example: Model #: SLM7525B = SLM .750" x 2.25MHz BNC, or PT# T-8060-1878

SINGLE ELEMENT CONTACT TRANSDUCERS (SLF) – MEMBRANE



Element Size (Dia.)	A	B
.500"	1.250"	1.180"
1.00"	1.500"	1.580"



Description:	Replaceable membrane protected contact transducers.
Used:	Rough surfaces, Castings (provides better contact).
Damping:	High Gain
Connectors:	BNC
Price:	\$455.00 US **\$505.00 (P) Composite option - 1MHz & 3.5MHz only available with Composite.

Element Size	**1.0 MHz	**2.25 MHz	**3.5 MHz	***5.0 MHz
.500" DIA.	PSLF501 T-8041-0868	SLF5025 T-8041-1878	PSLF5035 T-8041-9868	SLF5050 T-8041-2878
1.00" DIA.	PSLF101 T-8071-0868	SLF1025 T-8071-1878	PSLF1035 T-8071-9868	SLF1050 T-8071-2878


Ordering Example: Model #: PSLF101 = PSLF 1.00" x 1.0 MHz, or PT# T-8071-0868

SINGLE ELEMENT CONTACT TRANSDUCERS (FC) – FINGER TIP



Description:	General contact style transducers with stainless steel construction. Good for near surface resolution with a 70% bandwidth.
Used:	Common metals, plastics
Damping:	High gain (G), Resolution (R) *Specify damping after (FC), No Damping on 1MHz or 3.5MHz - Composite.
Connectors:	Microdot Side Entry *Optional top connect (T)
Price:	\$375.00 US or **\$400.00. 1MHz & 3.5MHz only available with Composite. \$410.00 (P) Composite option. *Specify connector mount after model #, or use direct part #


Element Size	1.0 MHz	2.25 MHz	3.5 MHz	5.0 MHz	**10.0 MHz
.250" DIA.	-	FC2525 T-4023-1855 (R) T-5023-1855 (T) T-4023-1845 (G) T-5023-1845 (T)	PFC2535 T-4023-9865 T-5023-9865 (T)	FC2550 T-4023-2855 (R) T-5023-2855 (T) T-4023-2845 (G) T-5023-2845 (T)	FC2510 T-4023-4855 (R) T-5023-4855 (T) T-4023-4845 (G) T-5023-4845 (T)
.375" DIA.	-	FC3725 T-4033-1855 (R) T-5033-1855 (T) T-4033-1845 (G) T-5033-1845 (T)	PFC3735 T-4033-9865 T-5033-9865 (T)	FC3750 T-4033-2855 (R) T-5033-2855 (T) T-4033-2845 (G) T-5033-2845 (T)	FC3710 T-4033-4855 (R) T-5033-4855 (T) T-4033-4845 (G) T-5033-4845 (T)
.500" DIA.	PFC501 T-4043-0865 T-5043-0865 (T)	FC5025 T-4043-1855 (R) T-5043-1855 (T) T-4043-1845 (G) T-5043-1845 (T)	PFC5035 T-4043-9865 T-5043-9865 (T)	FC5050 T-4043-2855 (R) T-5043-2855 (T) T-4043-2845 (G) T-5043-2845 (T)	FC5010 T-4043-4855 (R) T-5043-4855 (T) T-4043-4845 (G) T-5043-4845 (T)
Ordering Example: Model #: FCR5025 = FC Resolution .500" x 2.25MHz, or PT# T-4043-1855					

SINGLE ELEMENT CONTACT TRANSDUCERS (FCSL) – FINGER TIP (SLIM LINE)					
					
Description:	Line high frequency general contact transducers with a stainless steel housing.				
Used:	Common metals, plastics				
Damping:	High Damped				
Connectors:	Microdot Side Entry *Optional top connect (T)				
Price:	See below *Specify connector mount after model #, or use direct part #				
Element Size	5.0 MHz	10.0 MHz	15.0 MHz	20.0 MHz	
Price	\$435	\$465	-	-	
.125" DIA.	FCSL1250 T-4903-2875 T-5903-2875 (T)	FCSL1210 T-4903-4875 T-5903-4875 (T)	FCSL1215 -	FCSL1220 -	
Ordering Example: Model #: FCSL1250 = FCSL .125" x 5MHz, or PT# T-4903-2875					

Accessory Items

Instrument & Carrying Cases			
			
Part #	Description	Comments	Price \$
F-149-0001	PMX, PVX Series Instrument Case	Nylon	90.00
A-149-6002	PMX, PVX Series Instrument Case	Rubber	115.00
A-100-6003	Plastic Carrying Brief Case	PMX/PVX	45.00

Transducer Cables			
			
Custom Lengths & High Temp/Wear Teflon: Available on request.			
Part #	Description	Comments	Price \$
N-104-0070	4' Single Lemo to Microdot	All Gauges	70.00
N-106-0100	6' Single Lemo to BNC	All Gauges	75.00
N-104-0020	4' Single Lemo to Microdot	All Gauges	80.00
N-106-0020	6' Single Lemo to BNC	All Gauges	80.00
N-110-0020	10' Single Lemo to Microdot	All Gauges	85.00
N-120-0020	20' Single Lemo to Microdot	All Gauges	95.00

Couplant			
			
Part #	Description	Comments	Price \$
V-000-0001	4 oz bottle		20.00
V-000-0003	12 oz bottle		30.00
V-000-0004	1 gallon		180.00
V-000-0005	4 oz bottle (low viscosity) - standard	HPD - Delay Line	25.00

Calibration Blocks



***Custom composite materials not available**

Part #	Description	Mat'l Type	Price \$
X-000-0001	5 Step - .100" to .500"	4340 Steel	235.00
X-000-0002	4 Step - .250 to 1.0"	4340 Steel	235.00
Custom	5 Step - .100" to .500"	1018 Steel	235.00
Custom	4 Step - .250 to 1.0"	1018 Steel	235.00
X-000-0022	5 Step - 2.5 - 12.5mm	1018 Steel	255.00
X-000-0021	4 Step - 6.25 - 25.0mm	1018 Steel	255.00
Custom	5 Step - .100" to .500"	7075 Aluminum	235.00
Custom	4 Step - .250 to 1.0"	7075 Aluminum	235.00
Custom	5 Step - .100" to .500"	304 Stainless Steel	530.00
Custom	4 Step - .250 to 1.0"	304 Stainless Steel	530.00
Custom	5 Step - .100" to .500"	Titanium	595.00
Custom	4 Step - .250 to 1.0"	Titanium	595.00
X-000-0005	Carrying case	Wood	60.00

Data Cables

Part #	Description	Comments	Price \$
N-003-0330	USB-C to USB TYPE A 3' data cable	v2.0 gauges	30.00